



## Be unique Stylish and flawless POS printers



## CITIZEN CT-S251 POS

### Applications

- Receipt
- Queue management
- Weigh scales
- Coupon
- Daily report
- Hospitality

### Fast and chic

With its unique and stylish design, the two-inch CT-S251 POS printer is perfect for receipt or queue management systems. With a class-leading 300 mm/s print speed and a front exit, compact size, the CT-S251 blends performance and poise.

Connectivity is key with the possibility for USB, Serial, MFi Bluetooth, Ethernet and WiFi interfaces and toolkit support for iOS, Android and Windows operating systems.

The CT-S251 is perfect for high class restaurant and boutiques where the environment requires a top class POS printer with eye-catching design.



**Interface Connections**  
Choose to install an MFi Bluetooth, USB, Serial, Ethernet or WiFi interface and the standard cash drawer kicker.



## Specifications

|                             |           |  |
|-----------------------------|-----------|--|
| Printing method             |           | Line Thermal Dot Printing  |
| Printing width              |           | 54mm/432 dots  |
| Dot structure               |           | 432 dots/line (up to 436 dots)   |
| Dot pitch                   |           | 8 dots/mm (203 dpi)  |
| Printing characters         |           | Up to 36 digits (12 × 24: font A), Up to 48 digits (9 × 24: font B), Up to 54 digits (8 × 16: font C)  |
| Printing speed              |           | Up to 300mm/sec., When greyscale printing: 130mm/sec   |
| Paper feed                  |           | Feed pitch 0.125mm   |
| Line feed width             |           | 4.23mm (1/6 inch) user-configurable  |
| Barcode type                |           | UPC-A, UPC-E, JAN / EAN-8, JAN / EAN-13, ITF, CODE39, CODE93, CODE128, CODABAR (NW-7), PDF417, QR Code, GS1 Databar.   |
| Emulation                   |           | ESC/POS™®  |
| Paper                       | Width     | 57.5 ± 0.5 mm  |
|                             | Diameter  | 83mm or less   |
|                             | Thickness | 53µm to 85µm   |
| Recommended Paper           |           | Mitsubishi Paper Mills P220AG normal type 65, HP220AB-1 highly conserved type 75, F230AA normal type 65, P220AB normal type 85, Oji Paper PD150R normal type 75, PD160R high storage type 65/75, Nippon Paper TF50KR-2Y high storage type 62, TR50KJ-R high-save type 63 |
| <b>Power specifications</b> |           |  |
| Power adapter               |           | 37AD2 (A: AC adapter type)   |
| AC Input voltage            |           | AC 100 to 240V, 50/60 Hz, 150 VA   |
| Operation voltage           |           | 24V DC ± 7%  |
| Standby current             |           | About 0.1A   |
| Weight                      |           | 1.20 Kg  |
| Dimension (W x D x H)       |           | 108 x 165 x 108 mm footprint. +5mm front lip   |
| Operating environment       |           | +5 to +45°C, 10% - 90% RH, non condensing  |
| Storage environment         |           | -20 to +60°C, 10% - 90% RH, non condensing   |

All product names are trademarks of the respective manufacturers. ESC/POS™® are trademarks or registered trademarks of Seiko Epson Corporation. Android™ is a trademark of Google Inc., IOS™ is a trademark of Cisco Systems. Windows® is either a registered trademark or trademark of Microsoft Corporation. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded.

## CITIZEN CT-S251 POS

### Features & Benefits

- Front Exit
- Fast 300 mm/sec
- 2-inch media: 57.5 ± 0.5 mm
- MFi / iOS Bluetooth version
- WiFi and Ethernet versions
- Energy Star power supply
- Stylish black or white case
- Same height as cash drawers
- Cash drawer connection
- ESC/POS™® compatibility
- SDKs for iOS, Android, Windows

