



Mobilize Your Enterprise®

# DPP-350

## GENERAL SPECIFICATIONS

### ► PRINTING SPECIFICATIONS



PRINTING METHOD	Line thermal dot printing
PRINTING SPEED	60mms/s (480 dots/sec) at 8.5 V
PRINT WIDTH	72mm / 576 dots per line
RESOLUTION	203dpi (8x8 dots/mm)
PRINTING SPEED	0.125 mm (8 dots/mm)
LOGO RESOLUTION	1 black and white size: 576 x 248 dots
INPUT BUFFER	36,864 bytes
EMULATION	ESC/POS Continuous paper mode
RELIABILITY	Printing head: 50km (printing rate 25% max)

RESIDENT BARCODES	<b>1D:</b> EAN13, EAN8, UPC-A, UPC-E, Codebar, Code39, Code128
	<b>2D:</b> PDF417, QR Code

THERMAL PAPER	<b>Paper Width:</b>
	<b>Paper Thickness:</b>
	<b>Paper Outer Diameter:</b> 78mm +0/-1mm X 50mm diameter, 57 mm x 50 mm diameter (option)

FONTS	DEFAULT	<b>Font A:</b> 12 x 24 dots (48 char. per line)
		<b>Font B:</b> 9 x 16 dots (64 char. per line)
	LOADABLE	<b>Font C:</b> 12 x 24 dots (48 char. per line)
		<b>Font D:</b> 9 x 16 dots (64 char. per line)

### ► MECHANICAL

COMPATIBILITY	iOS6 and higher
DIMENSIONS (LxWxH)	118mm X 90mm X 51mm (4.6" X 3.5" X 2")
WEIGHT	340 grams (.75lbs) without paper

### ► ELECTRICAL

BATTERY CAPACITY	per charge (~30,000 lines)
BATTERY LIFE	Rechargeable Li-ion battery (7.4 V / 2000 mAh)
POWER SUPPLY AC ADAPTOR	DC 9 V, 1 A AC 100 - 240 V, 1.3 A, 50/60 Hz

#### Mobility Sales/Technical Center

1641 McGaw Avenue  
Irvine, CA 92614  
O 949.222.0300  
T 877.278.7860  
F 949.222.0375

#### Headquarters/Main Warehouse

2312 Touhy Avenue  
Elk Grove Village, IL 60007  
O 847.818.1260  
T 877.278.7860  
F 847.818.1287

#### Infinite Peripherals Canada

677 MacDonald Avenue, Unit #210  
Sault Ste Marie, ON  
P6B 1J4 Canada  
O 705.943.1808  
E canada [at] ipcprint.com

#### ipcmobile.com

Specifications subject to change without notice. Infinite Peripherals, Mobilize Your Enterprise, Linea Pro, Infinea, Infinea Tab and Infinea Omni are trademarks of Infinite Peripherals, Inc. All other trademarks are the property of their respective owners.

© 2016 Infinite Peripherals, Inc.

► ENVIRONMENTAL

---

OPERATING ENVIRONMENT

+0°C to +45°C 35 to 85% RH

---

STORAGE ENVIRONMENT

-20°C to +60°C 10 to 90% RH