


M2-490DS-A1

49" Digital Signage Touch Monitor




Description

The new M2-490DS-A1 49" interactive touch monitor is a newly designed solution for a variety of applications. Engineered with optical bonding between the sensor and LCD, improving optical clarity, adding strength and impact resistance, while increasing touch accuracy. The M2-490DS-A1 features a premier anti-glare finish, driving better light dispersion and viewing performance in high ambient light applications. Supporting more than 55 touch points, multiple styli and erasers, this display is a drop-in solution for not only retail/hospitality signage and wayfinding, but collaboration applications as well. Combining the ultra-slim design, enhanced anti-glare finish, the versatile I/O selection, peak optical performance with 4k resolution, this display is a solution that can exceed a wide range of application requirements.

Featured Specifications

- Size: 49" TFT LCD
- Maximum Resolution: 3840 x 2160
- Contrast Ratio: 1200:1
- Aspect Ratio: 16:9
- Brightness: 500 nits (No Touch), 450 nits (P-CAP)
- View Angle: H: 178°, V: 178°
- Video Port: 2 x HDMI/1 x DisplayPort/1 x VGA
- Warranty: 3 year
- TAA compliant



Specifications

Touch LCD Display

Touch Screen	Projected Capacitive
Touch Points	>55 (with stylus support)
Touch Screen Interface	USB-HID (Type B)
Surface Treatment	Anti-Glare, Optical Bonding

I/O Ports

Serial Port	1 x RS232 (DB9)
USB Port	2 x USB Type B (touch) 1 x USB 2.0 Type A
Video Port	2 x HDMI / 1 x DisplayPort / 1 x VGA
Audio Port	PC Audio in/out, SPDIF out
Network Port	1 x RJ45
Power Input	AC Input 100~240Vac, 50~60Hz
Power Output	AC output IEC C13 type

Physical Properties

Power Supply	135 W Typ.
Speaker	10W x 2
Orientation	Portrait/Landscape/Tabletop
Housing Color	Black
Construction	Glass, SECC Metal
Compliance	IP65 – Front only
Dimensions – W x H x D (mm)	1139.20 x 669.4 x 77.7 mm
Net Weight (kg)	26 kg
Carton – W x H x D (mm)	1290 x 786 x 173 mm
Gross Weight (kg)	31 kg
VESA	400 x 400 mm
Ball Drop	IK06

Safety

Certifications	FCC/CE/UL/CEC/UKCA/ETSI EN 303 645
----------------	------------------------------------

Environment

Operating Temperature	0°C ~ 40°C, 35% ~ 85%, RH. Non-Condensing
Storage Temperature	-20°C ~ 60°C, 35% ~ 85% RH. Non-Condensing



www.MicroTouch.com | us.orders@microtouch.com

MicroTouch Interactive, Inc.
200 East Broadway Avenue, Maryville, TN 37804 | (616) 786-5353

The information presented in this specification sheet is intended as general information about MicroTouch products and is subject to change. Product specifications and warranties will be governed by MicroTouch Interactive, Inc. standard terms and conditions of sale. Products are subject to availability. Copyright © 2025 MicroTouch Interactive, Inc. All rights reserved. MT25-1246 - 060926