

Elo Backpack® 5

Android™ Computer









Product Overview

The Elo Backpack 5 delivers a powerful, enterprise-grade computer complete with a flexible Android 14 OS, powerful Qualcomm 6490 processor, WiFi 6E and connectivity to satisfy all your needs. Purpose-built to fit in compact spaces, the Elo Backpack boasts a small footprint in both size and weight and can secure to any counter or in a kiosk easily with the built-in 75 mm or 100 mm VESA mount.

From signage and kiosks to automation controls, the Elo Backpack is designed to simplify the deployment of content, websites and Android-based apps across your interactive experiences. Scaling Elo's commercial Android platform across sizes and form factors has never been easier.

Connectivity includes HDMI, USB 3.0, USB-C, Ethernet, Bluetooth, Wi-Fi, micro-SD and GPIO

EloView ready - seamlessly manage and update digital content across multiple locations with ease

Enterprise-Grade Support - Security updates, seamless provisioning, Elo Home, OEMConfig and more

Elo Backpack 5

| Specifications | | | | | |
|---|---|--|--|--|--|
| Enclosure Color | Black | | | | |
| Android 14 with Google Play Services and EloView content deployment and management Planned upgrade to Android 16 and Android 18 are available with an OS 360 subscription | | | | | |
| Processor | Qualcomm Snapdragon QCS6490 | | | | |
| Memory (RAM) | 8GB | | | | |
| Storage | 64GB | | | | |
| IO Ports | HDMI, 4x USB 3.0 support, Type C USB output, Micro SD slot, GPIO, Ethernet 1x LAN (Gigabit), DC in | | | | |
| Wireless | 802.11a/b/g/n/ac/ax + Bluetooth 5.2 (Via external antenna) | | | | |
| Max Resolutions | USB-C*: 1920 x 1080 @60fps HDMI: 3840 x 2160 @60fps * When using USB-C for video, the USB protocols will be dropped to 2.0 speeds. | | | | |
| Power Input AC input voltage: 100-240 VAC; Input frequency: 50-60 Hz | | | | | |
| Power Consumption (Typical) | On: 4.1W; Off: 0.1W; Sleep: 3.8W | | | | |
| Dimensions | 4.5" x 5.5" x 1.0" / 114 mm x 139 mm x 25.4 mm | | | | |
| Shipping Dimensions | Individual System: 14.6" x 8.3" x 2.4" / 371 mm x 210 mm x 62 mm 8 systems in 1 carton: 17.4" x 10.6" x 16.3" / 441 x 270 x 413 mm Unpackaged: 1.3 lbs / 0.59 kg Packaged (Individual System): 2.9 lbs / 1.3 kg Packaged (8 systems in 1 carton): 26.0 lbs / 11.8 kg | | | | |
| Weight | | | | | |
| Temperature | Operating: 0°C to 40°C (32°F to 104°F) Storage: -20°C to 50°C (-4°F to 122°F) | | | | |
| Humidity (non-condensing) Operating: 20% to 80%; Storage: 10% to 90% | | | | | |
| Mounting Options | VESA 75mm and 100mm | | | | |
| Real-Time Clock | Lithium coin cell battery for real time clock | | | | |
| Regulatory Approvals and Declarations | UL/cUL (US); FCC (US); IC (Canada); CE (Europe); CB (International); VCCI, MIC (Japan); RCM (Australia); BSMI/NCC (Taiwan); KCC (Korea); CCC/SRRC (China) | | | | |
| Supported Country List | Canada, USA, Australia, Japan, New Zealand, Austria, Belgium, Czech Republic, Denmark, France, Germany, United Kingdom, Hungary, Italy, Netherlands Poland, Portugal, Romania, Spain, Sweden, Switzerland, Turkey | | | | |
| Warranty | 2 years | | | | |
| Extended Warranty | 3 year OS 360 - Elo P/N: E897877, 4 year OS 360 - Elo P/N: E898079, 5 year OS 360 - Elo P/N: E898282 ed Warranty 3 year - Elo P/N: E895914, 4 year - Elo P/N: E896120, 5 year - Elo P/N: E896322 2 year + AUR - Elo P/N: E896513, 3 year + AUR - Elo P/N: E896699, 4 year + AUR - Elo P/N: E896903, 5 year + AUR - Elo P/N: E897104 | | | | |
| OS Support | Bi-monthly Android security updates available with Elo OS 360 package. | | | | |
| What's in the Box | Elo Backpack, North American Power Cable, European Power Cable, 1x Power Brick with locking screw, 2x Antenna, Quick Install Guide, 4x Screws (M4x30mm), 4x Screws (M4x35mm) | | | | |

Ordering Information

| Part Number | Processor | os | Memory | Storage |
|-------------|------------------|------------|--------|---------|
| E620713 | Qualcomm QCS6490 | Android 14 | 8GB | 64GB |

Learn more about Elo at ${\bf EloTouch.com}.$

Americas Europe (EMEA)

Tel +1 408 597 8000 Tel +32 16 930 136
elosales.na@elotouch.com EMEA.Sales@elotouch.com

Asia Pacific

Tel +86 (21) 3329 1385 EloAsia@elotouch.com



