

SRP-S200

2-inch Linerless Pritner



Print Characteristics

Print Method

Direct Thermal (Front Exit)

Print Speed

Up to 150 mm/sec

Print Resolution

203 dpi

Print Width

Up to 54/32 mm

Sensor

Paper End, Black Mark, Cover Open, Paper Taken

Media Characteristics

Media Type

Linerless Restick

Media Width

58 mm

Optional 40 mm using Partition.

Media Roll Diameter

Up to 103 mm

Media Thickness

0.06 to 0.09 mm

Supply Method

Easy Paper Loading

Physical Characteristics

Dimensions (W x L x H)

128 x 156 x 196 mm (5.03 x 6.14 x 7.71 inch)

Weight

1.8 kg (3.96 lbs.)

Electrical

EnergyStar® Certified,
External Power Supply Housed Internally
(Adapter 24 V/2.5 A)

Performance Characteristics

NV Image Memory

768 Kbytes (Mono)

Receive Buffer

4 Kbytes

User Define Buffer

12 Kbytes

Interface

USB 2.0 FS + Ethernet + Serial

Environment Characteristics

Temperature

Operating: 0 to 40°C (32 to 104°F)

Storage: -20 to 60°C (-4 to 140°F)

Humidity

Operating: 10 to 80% RH

Storage: 10 to 90% RH

Sealing

IP23

Software

Emulation

BXL/POS™

Driver/Utility

Windows® Driver, OPOS/JPOS Driver,

Linux®/macOS® CUPS Driver,

Virtual COM USB/Ethernet Driver,

Utility Program, Network Auto Installer

Developer Tools

Android™/iOS®/Windows SDK, Linux SDK,

Xamarin SDK, Web Print SDK

(Android/iOS/Windows/macOS),

Cordova Plugin,

MAUI SDK, Flutter™ Plugin, React Native SDK

Design & Print

mPrint App (Android/iOS)

Fonts/Graphics/Symbologies

Character Size

Font A: 12 x 24, Font B: 9 x 17,

Font C: 9 x 24, KOR, CHN, JPN: 24 x 24

Characters per Line

Font A: 36,

Font B, C: 48, KOR, CHN, JPN: 18

Character Sets

Alphanumeric: 95

Extended Graphics: 128 x 35 page

International: 32

Barcode Symbologies

1D: Coda Bar, Code 39, Code 93,

Code 128, EAN-8, EAN-13, ITF,

UPC-A, UPC-E

2D: Data Matrix, PDF417, QR code

Accessories/Supplies

Included in the Box

Power Cord, 40 mm Partition,

USB A-B Cable 1.8 m

Options & Accessories

External Buzzer, B-Melodist,

USB to Serial Cable, Serial Cable (9-9 pin)

Compatible Supplies

B-linerless™